

Boomlift / Manlift

Used Boom Lift Corona - In terms of popular aerial machinery, the boom lift is one of the most recognizable. Commonly known as aerial work platforms, mobile elevating work platforms, cherry pickers, aerial devices and elevating work platforms, it was engineered to complete work at higher locations more efficient and easier. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Workers need to remain safe as they access locations at higher altitudes. The material handling industry offers many boom lift models. Most boom lifts can be successfully run with a single operator. This machine is popular for harvesting fruit in locations such as orchards that historically relied on climbing dangerous ladders. Since ladders require even, solid ground for setting them up safely, they can be unreliable in the agricultural industry. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder. Gaining Access Over Obstacles Certain boom lifts are designed to move up and over items. This makes working over obstacles possible Having the capacity to reach an object even when you are unable to maneuver the equipment directly underneath has a variety of applications including window cleaning, telephone pole and line installation and service, fixing overhead cables and numerous other industries. Articulated boom lifts are comprised of many joints that allow the machine to bend under or over obstacles. To enable operators to access many places, these sections of the boom lift can move independently. This equipment is popular in narrow storage locations and hallways thanks to its' tight turning radius. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts These boom lifts are popular for numerous construction and maintenance jobs. They provide a vital piece to the fleet for servicing power lines and overhead wires. Certain models are outfitted with water cannons to be used in firefighting applications. Maximum reach can be attained with telescoping boom sections on certain models. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. The nickname "spiders" has been given to these boom lifts due to their legs which can support the machine on rough or steep terrain. Capable of fitting through doorways, interior articulating boom lifts are more compact and used commonly in storage, retail and warehousing applications. Electric models are preferred in interior situations due to the danger that carbon monoxide exhaust poses and how much quieter these models are. Telescopic Boom Lifts Articulating boom lifts and telescopic boom lifts move differently from each other. These units use hydraulics to retract and extend outwards and upwards. The worker who is in the platform has the controls to extend the lift and is able to operate without a second worker. Some taller and larger models have a jib situated near the top that is similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. With 4WD options and their capacity to travel through small spaces, boom lifts are used in a variety of industries. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Certain boom lift models have a jib or an extension located between the platform and the end of the main boom. This enables extra reach and another articulation point or hinge for the platform to move side-to-side or up-and-down. Articulating boom lifts and telescopic boom lifts may have jibs. Articulating models have a joint situated roughly halfway between the wheels and the platform to enable it to reach over an obstacle and then lower again if required. Genie Articulating Boom Lifts A popular type of articulating boom lift manufactured on the market is the Genie Z-boom Model. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. The first articulating Genie Z-30/20 boom was launched in 1985. These machines became immediately popular with their up-and-over design that continues to make them sought after nowadays. Proper Safety Measures When

operating any type of industrial equipment, safety is first and foremost. It is essential that all potential safety hazards are known to anyone working within the area to maintain a safe atmosphere. Safe operation of the machine and personal safety must be paramount. Proper safety gear and communication need to be completed prior to operating. Prior to operating, ensure there are no open flames, combustible or flammable items, lit cigarettes, battery gases or engine fuels present. For the ultimate safety, it is important to have a visible, safely mounted and accessible fire extinguisher within the operators reach. Keep work surfaces and charging stations clean and free from clutter or tools that could puncture the tires or damage the machine or its components. Daily Maintenance Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. Stabilizing the weight is accomplished supportive devices to lift and distribute the load. Straps, fasteners and chains need to be checked they are in good condition. It is very dangerous to reuse single use fasteners and other components as they might fail if used beyond their recommendations. It is vital to discard oils and solvents safely and efficiently to prevent contaminating the environment. Safety can be increased with proper lighting and adequate ventilation along workbenches and within workshops and garages. To organize and specify, maintenance is categorized into a variety of subsections including Annual Maintenance, Quarterly Maintenance, Programmed and Commissioning Maintenance Intervals. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Not complying with routine maintenance can put the operator at a huge safety risk, lead to damaged components, terrible performance and preventable downtime. A large part of keeping the boom lift secure and operational is the maintenance inspection report that ensures the operator is safe and monitors the machine's performance and service. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. Annual and Quarterly maintenance procedures need to be performed once or multiple times a year. Maintenance procedures are based on the operating hours of the boom lift and programmed maintenance may be conducted during pre-delivery machine preparation. Set yourself up for success by consulting your maintenance manual before operating the equipment to ensure battery life, oil changes and fluid levels are ready to go.